

Lectodara 7000

Automatic System of Data Capture



RELIABLE

FAST

MODULAR

MINIMUM MAINTENANCE

From paper to your database®

www.dara.es/omr

Avenida del Levante, 7
28016 Madrid (Spain)
Teléfono: +34 915 155 247 Móvil: +34 606 068 558
Fax: +34 915 155 248 E-mail: omr@dara.es



Lectodara 7000

LECTODARA 7000 WITH SORTER



LECTODARA 7000
WITHOUT SORTER



Main Applications:

Education: Exams, surveys, income, absences.

Medicine: Health surveys, psychological, clinical analysis.

Company: Climate surveys, 360°, quality control, satisfaction.

Other: Oppositions, election processes, job reports, records, tasting, censuses, instances, lotteries, games, and more.



Lectodara 7000: Automatic System of Data Capture

Optical Mark Reader, validator of documents in real time.
Exceptional solution: Robust, reliable, fast.

Features

Paper	Thickness	72 gr – 135 gr	
	Minimum size	63,5 x 110 mm	
	Maximum size	228.6 x 355.6 mm	
Speed	Feeding speed	RS232C; 5.300 sheets/ h USB 2.0; 5.300 sheets /h	
	Reading speed	5.300 sheets per hour (USB 2.0)	
Function	Initial setting	Control Panel	
	Electric tuning	Control Panel	
	Display	LCD	
	Operation switch	5	
	PC connection	Defined automatically	
	PC interface	RS-232C USB 2.0	
Mark	Sensor Type	1/6" , 0.2" , 0.25" , 0.3"	
	Light source	Infrared or visible	
	Reading method	Direct under, Mark to mark	
	Maximum number of Line	48	
	Maximum number of row	80	
Hopper	Capacity	500 sheets	
Reject	Capacity	500 sheets of /150 sheets	
Option	ADF	Standard	
	Printer	Standard	
	Select Stacker	Standard	
	Double sides	Available	
	Bar-code	Vertical Horizontal	
	(Specification of Bar-codea)	JAN, EAN, UPC NW7, ITF. CODE-39 (V: industrial 2 de 5, COOP 2 de 5) (H: EAN-128 CODE-93)	
	Size	Dimensions	365x490x800
		Weight (kg)	36Kg
	Regulation	UL approval	Yes
		CE approval	Yes
BSMI		Yes	

Software included: Evaldara. (Optional: Integra)